



UL 3386

Product Description

 Rated voltage
600V

 Rated temperature
105°C

 Fire Performances
Horizontal flame

 AWG
32AWG-4/0AWG

 ²⁹CU Conductor
Solid / Stranded

 Insulation
XLPE

 Shield
Optional

 Jacket
Optional (PVC)

 Bend Radius
10X

Marking Example:
E209277 cUL AWM STYLE 3386 105°C 600V FT2 □□AWG
3A AWM IA 105°C 600V □□AWG FT2 3A LF



XLPE Insulation(XLPE導體) Conductor(導體)



Conductor			Insulation	
AWG 線規	Stranded (No./mm) 線規/線徑	Diameter (mm) 絞合外徑	Insulation Thickness (mm) 絕緣厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
4/0	2146/0.254	15.70	2.09	17.77±0.1
3/0	1615/0.254	13.65	2.09	15.97±0.1
2/0	1330/0.254	12.36	2.09	14.88±0.1
1/0	1026/0.254	10.85	2.09	13.58±0.1
2	665/0.254	8.74	1.58	10.73±0.1
4	420/0.254	6.94	1.58	9.18±0.1
6	259/0.254	5.46	1.58	7.89±0.1
8	161/0.254	3.72	1.20	6.12±0.1
10	105/0.254	3.01	0.82	4.65±0.1
12	65/0.254	2.37	0.82	4.01±0.1
14	41/0.254	1.88	0.82	3.60±0.1
16	26/0.254	1.50	0.82	3.20±0.1
18	34/0.18	1.21	0.82	2.86±0.1
20	21/0.18	0.95	0.82	2.60±0.1
22	17/0.16	0.76	0.82	2.41±0.1
24	11/0.16	0.62	0.82	2.26±0.1
26	7/0.16	0.49	0.82	2.13±0.1
28	7/0.127	0.39	0.82	2.03±0.1
30	7/0.10	0.31	0.82	1.95±0.1
32	7/0.08	0.24	0.82	1.89±0.1

AWM UL 758

3A Plus, 3a plus (logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners