



## 30V XLPE Wire

## UL 3464

## Product Description

Rated voltage

30V



Rated temperature

125°C



Fire Performances

Horizontal flame



AWG

40AWG min



Conductor

Not Specified



Insulation

XLPE



Jacket


Optional / ETFE



Bend Radius

10X

## Marking Example:

E209277 cUL AWM STYLE 3464 125°C 30V FT2 □□AWG  
3A AWM IA 125°C 30V □□AWG FT2 3A LF

Conductor		Insulation		OVERALL DIAMETER 完成外徑(mm)
AWG 線規	Stranded (No./mm) 線規/線徑	Insulation Thickness (mm) 絕緣厚度(mm)	Jacket (mm) 外被厚度(mm)	
4/0	2146/0.254	0.16	0.11	14.14±0.1
3/0	1615/0.254	0.16	0.11	12.33±0.1
2/0	1330/0.254	0.16	0.11	11.24±0.1
1/0	1026/0.254	0.16	0.11	9.94±0.1
2	665/0.254	0.16	0.11	8.11±0.1
4	420/0.254	0.16	0.11	6.65±0.1
6	259/0.254	0.16	0.11	5.27±0.1
8	161/0.254	0.16	0.11	4.26±0.1
10	105/0.254	0.16	0.11	3.55±0.1
12	65/0.254	0.16	0.11	2.91±0.1
14	41/0.254	0.16	0.11	2.42±0.1
16	26/0.254	0.16	0.11	2.04±0.1
18	34/0.18	0.16	0.11	1.76±0.1
20	21/0.18	0.16	0.11	1.50±0.1
22	17/0.16	0.16	0.11	1.31±0.1
24	11/0.16	0.16	0.11	1.16±0.1
26	7/0.16	0.16	0.11	1.03±0.1
28	7/0.127	0.16	0.11	0.93±0.1
30	7/0.10	0.16	0.11	0.85±0.1
32	7/0.08	0.16	0.11	0.79±0.1
34	7/0.06	0.16	0.11	0.73±0.1

AWM UL 758

3A Plus, 3a plus (logo), and 3A (logo) are trademarks.  
Other logos, product and/or Company names may be trademarks of their respective owners.<https://www.3awire.com/>

All Rights Reserved.

The information provided by 3A PLUS is intended for general informational purposes only and should not be construed as professional advice. While we strive for accuracy and completeness, we make no guarantees regarding the reliability, suitability, or availability of the information presented. Any reliance you place on such information is strictly at your own risk. We reserve the right to modify our products, services, and policies at any time without prior notice. For specific inquiries or concerns, please contact us directly. Thank you for choosing 3A PLUS Wire &amp; Cable.