



UL 10272

Product Description

 Rated voltage
150V

 Rated temperature
80°C

 Fire Performances
Horizontal flame

 AWG
36AWG-20AWG

 **29** CU
Conductor
Solid / Stranded

 Insulation
PVC

 Bend Radius
10X

Marking Example:
E209277 cUL AWM STYLE 10272 80°C 150V FT2 □□AWG
3A AWM 1A 80°C 150V □□AWG FT2 3A LF



Conductor		Insulation		OVERALL DIAMETER
AWG	Stranded (No./mm)	Insulation Thickness (mm)	Covering (mm)	
線規	線規/線徑	絕緣厚度(mm)	外被厚度(mm)	完成外徑(mm)
20	21/0.18	0.21	0.13	1.63±0.10
22	17/0.16	0.21	0.13	1.44±0.10
24	11/0.16	0.21	0.13	1.29±0.10
26	7/0.16	0.21	0.13	1.17±0.10
28	7/0.127	0.21	0.13	1.07±0.10
30	7/0.10	0.21	0.13	0.98±0.10
32	7/0.08	0.21	0.13	0.92±0.10
34	7/0.06	0.21	0.13	0.86±0.10

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners