



600V PVC Wire

UL 1056

Product Description

 Rated voltage
600V

 Rated temperature
105°C

 Fire Performances
Horizontal flame

 AWG
20AWG-10AWG

 ²⁹CU Conductor
Solid / Stranded


 Insulation
PVC

 Bend Radius
10X

Marking Example:
E209277 cUL AWM STYLE 1056 105' 600V FT2 □□AWG
3A AWM IA 105°C 600V □□AWG FT2 3A LF



PVC Insulation (PVC 絕緣) Conductor(導體)



Conductor			Insulation	
AWG 線規	Stranded (No./mm) 線規/線徑	Diameter (mm) 絞合外徑	Insulation Thickness (mm) 絕緣厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
10	105/0.254	3.01	1.58	6.17±0.15
12	65/0.254	2.37	1.58	5.53±0.15
14	41/0.254	1.88	1.58	5.05 ±0.15
16	26/0.254	1.50	1.58	4.66±0.15
18	34/0.18	1.21	1.58	4.38±0.15
20	21/0.18	0.95	1.58	4.12±0.15

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners