



1000V PVC Wire

UL 11562

Product Description



Rated voltage

1000V



Rated temperature

105°C



Fire Performances

Horizontal flame



AWG

30AWG-2000kcmil



Conductor

Solid / Stranded



Insulation

PVC



Bend Radius


10X

Marking Example:

E209277 cUL AWM STYLE 11562 105°C 1000V FT2 □□AWG
3A AWM IA 105°C 1000V □□AWG FT2 3A LF

PVC Insulation (PVC 絕緣)

Conductor(導體)



AWG 線規	Conductor		Insulation		OVERALL DIAMETER 完成外徑(mm)
	Stranded (No./mm) 線規/線徑	Diameter (mm) 絞合外徑	Insulation Thickness (mm) 絕緣厚度(mm)		
4/0	2146/0.254	15.70	2.09		17.77±0.1
3/0	1615/0.254	13.65	2.09		15.97±0.1
2/0	1330/0.254	12.36	2.09		14.88±0.1
1/0	1026/0.254	10.85	2.09		13.58±0.1
2	665/0.254	8.74	1.58		10.73±0.1
4	420/0.254	6.94	1.58		9.18±0.1
6	259/0.254	5.46	1.58		7.89±0.1
8	161/0.254	3.72	1.20		6.12±0.1
10	105/0.254	3.01	0.82		4.65±0.1
12	65/0.254	2.37	0.82		4.01±0.1
14	41/0.254	1.88	0.82		3.52±0.1
16	26/0.254	1.50	0.82		3.20±0.1
18	34/0.18	1.21	0.82		2.86±0.1
20	21/0.18	0.95	0.82		2.60±0.1
22	17/0.16	0.76	0.82		2.41±0.1
24	11/0.16	0.62	0.82		2.26±0.1
26	7/0.16	0.49	0.82		2.13±0.1
28	7/0.127	0.39	0.82		2.03±0.1
30	7/0.10	0.31	0.82		1.95±0.1

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners