



300V SRPVC Wire

UL 1208

Product Description

 Rated voltage
300V

 Rated temperature
80°C

 Fire Performances
Horizontal flame

 AWG
30AWG-16AWG

 ²⁹CU
Conductor
Solid / Stranded

 Insulation
SRPVC

 Bend Radius
10X

Marking Example:
E209277 cUL AWM STYLE 1208 80°C 300V FT2 □□AWG
3A AWM IA 80°C 300V □□AWG FT2 3A LF



SRPVC Insulation (SRPVC 絕緣)

Conductor(導體)



Conductor			Insulation	
AWG 線規	Stranded (No./mm) 線規/線徑	Diameter (mm) 絞合外徑	Insulation Thickness (mm) 絕緣厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
16	26/0.254	1.50	0.39	2.28±0.1
18	34/0.18	1.21	0.39	1.99±0.1
20	21/0.18	0.95	0.39	1.73±0.1
22	17/0.16	0.76	0.39	1.54±0.1
24	11/0.16	0.62	0.39	1.39±0.1
26	7/0.16	0.49	0.39	1.27±0.1
28	7/0.127	0.39	0.39	1.17 ±0.1
30	7/0.10	0.31	0.39	1.09±0.1

AWM UL 758

3A Plus, 3a plus (logo), and 3A (logo) are trademarks.

Other logos, product and/or Company names may be trademarks of their respective owners