



600V XLPVC Wire

UL10222

Product Description

 Rated voltage
600V

 Rated temperature
105°C

 Fire Performances
Horizontal flame

 AWG

UL Labeled

 Conductor

UL Labeled

 Insulation

UL Labeled

 Shield

Optional

 Covering

PVC / XLPVC

 Bend Radius

10X

Marking Example:
E209277 cUL AWM STYLE 10222 105°C 600V FT2 □□AWG
3A AWM IA 105°C 600V □□AWG FT2 3A LF



XLPVC Covering (XLPVC外被)

XLPVC Insulation (XLPVC絕緣)

Conductor(導體)



Conductor		Insulation		OVERALL DIAMETER
AWG 線規	Stranded (No./mm) 線規/線徑	Insulation Thickness (mm) 絕緣厚度(mm)	Covering (mm) 外被厚度(mm)	
14	41/0.254	0.78	0.13	3.70±0.15
16	26/0.254	0.78	0.13	3.60±0.15
18	34/0.18	0.78	0.13	3.20±0.15
20	21/0.18	0.78	0.13	3.05±0.15
22	17/0.16	0.78	0.13	2.90±0.15

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners