



UL 21143

Product Description



Rated voltage

300V / 600V

Rated temperature

80°C

Fire Performances

Not Specified

AWG

26AWG-16AWG

Conductor

Solid / Stranded

Insulation

UL Labeled

Assembly

2-10 conductors (singles /twisted pairs / groups /laid parallel to form flat, oval, or round cables)



Shield

Optional


Jacket

FRPE / PE

Bend Radius

10X**Marking Example:**

E209277 cUL AWM STYLE 21143 80°C 600V FT2 □□AWG
3A AWM IA 80°C 600V □□AWG FT2 3A LF



AWG 線規	Conductor		Insulation			OVERALL DIAMETER 完成外徑(mm)
	Stranded (No./mm) 線規/線徑	Cores (N) 芯線(C)	Insulation overall Diameter(mm) 芯線直徑(mm)	Covering&Jacket of Thickness(mm) 外被厚度(mm)		
16	26/0.254	2	2.13	0.40	0.76	5.80±0.1
	34/0.18	2	1.84	0.40	0.76	5.30±0.1
18	34/0.18	3	1.84	0.40	0.76	6.00±0.1
	21/0.18	2	1.58	0.40	0.76	4.90±0.1
20	21/0.18	3	1.58	0.40	0.76	5.48±0.1
	21/0.18	4	1.58	0.40	0.76	5.97±0.1
22	17/0.16	2	1.40	0.40	0.76	4.61±0.1
	17/0.16	3	1.40	0.40	0.76	5.12±0.1
24	17/0.16	4	1.40	0.40	0.76	5.55±0.1
	11/0.16	2	1.25	0.40	0.76	4.36±0.1
24	11/0.16	3	1.25	0.40	0.76	4.82±0.1
	11/0.16	4	1.25	0.40	0.76	5.21±0.1
26	7/0.16	2	1.13	0.40	0.76	4.20±0.1
	7/0.16	3	1.13	0.40	0.76	4.60±0.1
28	7/0.16	4	0.13	0.40	0.76	5.00±0.1
	7/0.127	2	1.03	0.40	0.76	4.00±0.1
28	7/0.127	3	1.03	0.40	0.76	4.40±0.1
	7/0.127	4	1.03	0.40	0.76	4.70±0.1
30	7/0.10	2	0.94	0.40	0.76	3.90±0.1
	7/0.10	3	0.94	0.40	0.76	4.21±0.1
30	7/0.10	4	0.94	0.40	0.76	4.50±0.1

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.

Other logos, product and/or Company names may be trademarks of their respective owners

<https://www.3awire.com/>

All Rights Reserved.

The information provided by 3A PLUS is intended for general informational purposes only and should not be construed as professional advice. While we strive for accuracy and completeness, we make no guarantees regarding the reliability, suitability, or availability of the information presented. Any reliance you place on such information is strictly at your own risk. We reserve the right to modify our products, services, and policies at any time without prior notice. For specific inquiries or concerns, please contact us directly. Thank you for choosing 3A PLUS Wire & Cable.