



UL 21284

Product Description

 Rated voltage
30V

 Rated temperature
80°C

 Fire Performances
Cable flame

 AWG
40AWG min

 Conductor
Solid / Stranded


 Insulation
UL Labeled

 Assembly
2-more conductors (twisted pairs / groups / laid parallel to form flat, oval, or round cables)

 Shield / Covering
Optional
Optional / FRPE / PVC

 Jacket
FRPE

 Bend Radius
10X



AWG 線規	Conductor		Insulation			OVERALL DIAMETER 完成外徑(mm)
	Stranded (No./mm) 線規/線徑	Cores (N) 芯線(C)	Insulation overall Diameter(mm) 芯線直徑(mm)	Covering&Jacket of Thickness(mm) 外被厚度(mm)		
18	34/0.18	2	1.84	0.23	0.76	5.60±0.1
	34/0.18	3	1.84	0.23	0.76	7.60±0.1
20	21/0.18	2	1.58	0.23	0.76	5.000±0.1
	21/0.18	3	1.58	0.23	0.76	7.00±0.1
22	17/0.16	2	1.40	0.23	0.76	4.60±0.1
	17/0.16	3	1.40	0.23	0.76	6.50±0.1
24	11/0.16	2	1.25	0.23	0.76	4.20±0.1
	11/0.16	3	1.25	0.23	0.76	6.10±0.1
26	7/0.16	2	1.13	0.23	0.76	4.00±0.1
	7/0.16	3	1.13	0.23	0.76	5.90±0.1
28	7/0.127	2	1.03	0.23	0.76	3.90±0.1
	7/0.127	3	1.03	0.23	0.76	5.70±0.1
30	7/0.10	2	0.94	0.23	0.76	3.60±0.1
	7/0.10	3	0.94	0.23	0.76	5.50±0.1

AWM UL 758

3A Plus, 3a plus (logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners

Marking Example:
E209277 cUL AWM STYLE 21284 80°C 30V VW-1 □□AWG
3A AWM IA 80°C 30V □□AWG VW-1 3A LF

