



# UL 21307

## Product Description

 Rated voltage  
**300V**

 Rated temperature  
**80°C**

 Fire Performances  
**Horizontal flame**

 AWG  
**Not Specified**

 Conductor  
**Solid / Stranded**


 Insulation  
**UL Labeled**

 Assembly  
**2-more conductors (twisted singles  
/ groups /laid parallel to form flat,  
oval, or round cables)**

 Shield / Covering  
**Optional**

 Jacket  
**FRPE**

 Bend Radius  
**10X**



AWG 線規	Conductor		Insulation		
	Stranded (No./mm) 線規/線徑	Cores (N) 芯線(C)	Insulation overall Diameter(mm) 芯線直徑(mm)	Jacket of Thickness(mm) 外被厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
24	7/0.16	3	1.25	0.41	3.20±0.1
	7/0.16	4	1.25	0.41	3.50±0.1
28	7/0.127	6	1.03	0.41	3.40±0.1
	7/0.127	6	1.03	0.76	4.20±0.1
	7/0.127	8	1.03	0.41	3.70±0.1
	7/0.127	8	1.03	0.76	4.60±0.1

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.  
Other logos, product and/or Company names may be trademarks of their respective owners

**Marking Example:**  
E209277 cUL AWM STYLE 21307 80°C 300V FT2 □□AWG  
3A AWM 1A 80°C 300V □□AWG FT2 3A LF

