



UL 2517

Product Description

Rated voltage

300V



Rated temperature

105°C



Fire Performances

Cable flame



AWG

40AWG min



Conductor

UL Labeled



Insulation

UL Labeled



Assembly

2-more



Shield / Covering / Braid

Optional



Jacket

PVC



Bend Radius

10X

Marking Example:

E209277 cUL AWM STYLE 2517 105°C 300V VW-1 □□AWG
 3A AWM IA 105°C 300V □□AWG VW-1 3A LF



AWG 線規	Conductor		Insulation			
	Stranded (No./mm) 線規/線徑	芯線(C) 芯線直徑(mm)	Insulation overall Diameter(mm) 芯線直徑(mm)	Covering&Jacket of Thickness(mm) 外被厚度(mm)		OVERALL DIAMETER 完成外徑(mm)
14	41/0.254	3	2.40	1.14	0.76	9.00±0.10
18	34/0.18	2	1.73	1.14	0.76	6.00±0.10
22	7/0.16	2	1.28	1.14	0.76	4.60±0.10
	7/0.16	3	1.28	1.14	0.76	5.25±0.10
24	7/0.16	6	1.28	1.14	0.76	5.75±0.10
	11/0.16	4	1.13	1.14	0.76	5.30±0.10
	11/0.16	6	1.13	1.14	0.76	6.20±0.10
24	11/0.16	8	1.13	1.14	0.76	6.80±0.10
	11/0.16	10	1.13	1.14	0.76	7.60±0.10

AWM UL 758

3A Plus, 3a plus (logo), and 3A (logo) are trademarks.

Other logos, product and/or Company names may be trademarks of their respective owners

