




UL 20912

Product Description

**Rated voltage****30V / 90V / 150V / 300V / 600V****Rated temperature****60/75/80/90/105°C****Fire Performances****Horizontal flame / Cable flame****AWG****Not Specified****Conductor****Solid / Stranded****Insulation****UL Labeled****Assembly****Two groups of conductors are laid parallel****Shield / Covering****Optional****Optional / PVC****Jacket****PVC****Bend Radius****10X****Marking Example:**E209277 cUL AWM STYLE 20912 105°C 600V VW-1 □□AWG
3A AWM IA 105°C 600V □□AWG VW-1 3A LF

Conductor			Insulation		
Cores (N) 芯線	AWG 線規	Stranded (No./mm) 線規/線徑	ID(mm) 芯線直徑 (mm)	Jacket of Thickness(mm) 外被厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
2C	-	12	65/0.254	3.00	8.5±0.2
2C	UL3237	16	7/0.45	3.00	8.5±0.2
	UL10097	22	7/0.254	1.30	
4C	-	22	34/0.16	1.80	6.10±0.2

AWM UL 758

3A Plus, 3a plus (logo), and 3A (logo) are trademarks.

Other logos, product and/or Company names may be trademarks of their respective owners

