



# UL 20328

## Product Description

Rated voltage

**600V**



Rated temperature

**105°C**



Fire Performances

**Cable flame**



AWG

**36AWG min**



Conductor

**Solid / Stranded**



Insulation

**UL Labeled**



Assembly

**2 or more insulated conductors are cabled together to form a round, flat, or oval cable.**



Shield / Covering

**Optional**



Jacket

**TPE**




Bend Radius

**5X min.**

**Marking Example:**

E209277 cUL AWM STYLE 20328 105°C 600V VW-1 □□AWG  
3A AWM IA 105°C 600V □□AWG VW-1 3A LF



AWG 線規	Conductor		Insulation			OVERALL DIAMETER 完成外徑(mm)
	Stranded (No./mm) 線規/線徑	Cores (N) 芯線(C)	Insulation overall Diameter(mm) 芯線直徑(mm)	Jacket&Shield of Thickness(mm) 外被厚度(mm)		
14	41/0.254	2	2.96	1.15	0.16	7.46±0.15
	41/0.254	3	2.96	1.15	0.16	8.50±0.15
16	26/0.254	2	2.58	1.15	0.16	6.83±0.15
	26/0.254	3	2.58	1.15	0.16	7.78±0.15
18	34/0.18	2	2.30	1.15	0.16	6.37±0.10
	34/0.18	3	2.30	1.15	0.16	7.21±0.10
20	21/0.18	2	2.04	1.15	0.16	5.59±0.10
	21/0.18	3	2.04	1.15	0.16	6.69±0.10
22	17/0.16	2	1.85	1.15	0.16	5.63±0.10
	17/0.16	3	1.85	1.15	0.16	6.31±0.10

**AWM UL 758**

3A Plus, 3a plus (logo), and 3A (logo) are trademarks.

Other logos, product and/or Company names may be trademarks of their respective owners



<https://www.3awire.com/>

All Rights Reserved.

The information provided by 3A PLUS is intended for general informational purposes only and should not be construed as professional advice. While we strive for accuracy and completeness, we make no guarantees regarding the reliability, suitability, or availability of the information presented. Any reliance you place on such information is strictly at your own risk. We reserve the right to modify our products, services, and policies at any time without prior notice. For specific inquiries or concerns, please contact us directly. Thank you for choosing 3A PLUS Wire & Cable.