



# SAS High-Speed Cable Solutions



**Product Description**

Supports SAS 3/4, MiniSAS 8087 / 8643 Internal Interface, 100Ω Impedance



1M



HD MINISAS  
36M\*2 Cable,100Ω



miniSAS 36M\*2 Flat Cable,  
100Ω




HD miniSAS 36-SATA\*4+Sideband



miniSAS 26M-SATA 7\*4




Series miniSAS HD-29F\*4  
Cable



SAS32F 4ch. cable,75cm



SAS32F 4ch. cable,75cm



SAS32F-SATA 7F\*4, 75cm



SAS29F-SATA2+power, 70cm



MiniSAS 50M/ 36M\*2, 60cm

## Specifications

Item	Description
Signal Standard	SAS 3 / SAS 4
Impedance	100 Ω
Connector Types	SATA 7F, SAS26F / SAS32F / SAS36F / SAS50F, miniSAS 26M / 36M / 50M, MiniSAS HD
Cable Types	Host-to-Device, Multi-SATA Out, Sideband Included, Driver Extension
Customization	Various pinouts and lengths available (e.g., 48–100 cm)

All Rights Reserved.

The information provided by 3A PLUS is intended for general informational purposes only and should not be construed as professional advice. While we strive for accuracy and completeness, we make no guarantees regarding the reliability, suitability, or availability of the information presented. Any reliance you place on such information is strictly at your own risk. We reserve the right to modify our products, services, and policies at any time without prior notice. For specific inquiries or concerns, please contact us directly. Thank you for choosing 3A PLUS Wire & Cable.