



## 2000V PVC Wire

## UL1803

## Product Description

 Rated voltage  
**2000V**

 Rated temperature  
**80°C**

 Fire Performances  
**Horizontal flame**

 AWG  
**26AWG-18AWG**

 Conductor  
**Stranded**

 Insulation  
**PVC**

 Bend Radius  
**10X**

**Marking Example:**  
E209277 cUL AWM STYLE 1803 80°C 2000V FT2 □□AWG  
3A AWM IA 80°C 2000V □□AWG FT2 3A LF



PVC Insulation (PVC 絕緣)

Conductor(導體)



Conductor			Insulation	
AWG 線規	Stranded (No./mm) 線規/線徑	Diameter (mm) 絞合外徑	Insulation Thickness (mm) 絕緣厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
<b>18</b>	<b>34/0.18</b>	1.21	1.20	3.61±0.15
<b>20</b>	<b>21/0.18</b>	0.95	1.20	3.35±0.15
<b>22</b>	<b>17/0.16</b>	0.76	1.20	3.16±0.15
<b>24</b>	<b>11/0.16</b>	0.62	1.20	3.01±0.15
<b>26</b>	<b>7/0.16</b>	0.49	1.20	2.89±0.15

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.  
Other logos, product and/or Company names may be trademarks of their respective owners