



125V XLPVC Wire

UL 1472

Product Description

 Rated voltage
125V

 Rated temperature
80°C

 Fire Performances
Horizontal flame


 AWG
32AWG-20AWG

 Conductor
Solid / Stranded

 Insulation
XLPVC

 Bend Radius
10X

Marking Example:
E209277 cUL AWM STYLE 1472 125°C 80V FT2 □□AWG
3A AWM IA 125°C 80V □□AWG FT2 3A LF



Conductor			Insulation	
AWG 線規	Stranded (No./mm) 線規/線徑	Diameter (mm) 絞合外徑	Insulation Thickness (mm) 絕緣厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
20	21/0.18	0.95	0.82	2.60±0.15
22	17/0.16	0.76	0.82	2.41±0.15
24	11/0.16	0.62	0.82	2.26±0.15
26	7/0.16	0.49	0.82	2.13±0.15
28	7/0.127	0.39	0.82	2.03±0.15
30	7/0.10	0.31	0.82	1.95±0.15
32	7/0.08	0.24	0.82	1.89±0.15

AWM UL 758

3A Plus, 3a plus (logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners